# PANACAST 40 VBS

# The only small room Android™ bar that captures the entire room

› Everyone seen, every voice heard, nobody gets left out with180° field of view

› Flexible touch controller for desk or wall use

› Simple and fast installation

› Future proof investment, flexible deployment

| General info | | |
|---|---|---|
| | Box contents | PanaCast 40 VBS • Jabra Control IP • USB cable • power supply • wall mount • Privacy cover • 1 x HDMI cable 1.83m/6ft • 1 x regional power cable |
| | Main unit dimensions (WxHxD) | 530 x 105 x 60 mm \| 20.87 x 4.13 x 2.37 in |
| | Main unit weight (base unit) | 1.8 kg \| 3.9 lbs |
| | Warranty | 2 years |
| | Onboard AI | Yes |
| | Cable management | Yes |
| | Kensington lock compatible | Yes |
| | Operating voltage | 100-240V |
| | LED features and functions | Firmware update status, Mute/unmute, Power indicator, Streaming |
| | Certifications and compliance | ADA, Microsoft Teams Rooms, Zoom Rooms |
| | Room size | Certified for rooms up to 16' by 16' |
| **Video** | Video input | 1 x HDMI |
| | Supported display resolution | Supports up to 4K, Touch Display Compatible |
| | Camera resolution | 2 x 4K (2 x 8 megapixels) |
| | Number of cameras | 2 |
| | Content sharing | Apple Airplay (only supported by Zoom), HDMI input, Microsoft Teams-Cast (only supported by Teams) |
| | Type of camera | Dual camera panoramic |
| | Zoom | Up to 4x digital zoom |
| | Field of view | Horizontal: 180°, Vertical: 54° |
| | Intelligent Zoom | Yes |
| | Intelligent Meeting Space | Yes |
| | Multi-stream Dynamic Composition | Yes [1] |
| | Dynamic Composition | Yes |
| | Virtual Director | Yes |
| | Support secondary external USB camera | Yes |
| **Audio** | Speaker frequency range | 80Hz - 20000Hz |
| | Number of speakers | 1 |
| | Automatic Speaker Detection | Yes |
| | Noise Reduction Echo Cancellation | Yes |
| | Non-Speech Noise Suppression | Yes |
| | Number of microphones | 6 |
| | Microphone sensitivity | -37dBFS |
| | Microphone frequency range | 100Hz - 16000Hz |
| | Microphone pick up range | 4.5m \| 15ft |
| | Aux-Out | Yes |

| Category | Feature | Specification |
|---|---|---|
| **Security** | Media encryption | Provided by VaaS Partner |
| | Access management | Jabra+; Jabra WebConsole; Local account; VaaS Admin Portals including MS Teams Admin Center and Zoom Device Management |
| | Security management | Remote log in via Jabra+, Jabra WebConsole and VaaS Admin Portal |
| | Authenticated access to Admin settings, Jabra WebConsole, Jabra+ | Yes |
| | Account password strength check and enforcement | Yes |
| | Device locked down for security | Yes |
| | Lockdown with secureboot, OS verified boot, Vendor lock | Yes |
| | Log retrieval via Jabra Web Console | Yes |
| | Microsoft and Zoom based Vaas account authentication | Yes |
| **Connectivity** | Interfaces | USB-A, USB-C, Ethernet (RJ45), HDMI, Wi-Fi, 3.5mm jack port |
| | Bluetooth® version | 5.2 [2] |
| | Supported USB versions | USB 2.0, USB 3.0 |
| | USB cable length | 3m \| 9.8ft |
| **Network** | Internet Protocol (IP) | IPv4, IPv6 |
| | Ethernet | 10/100/1000 Mbps |
| | Auto-MDIX | Yes |
| | Proxy support | HTTPS |
| | Support DHCP | Yes |
| | Support Static IP Address | Yes |
| | Simple Certificate Enrollment Protocol | Yes |
| **Software & Apps** | Compatible software and/or apps | Jabra+; Jabra WebConsole for remote device management via HTTPs; Support for native 3rd party applications, including Microsoft Teams Room for Android and Zoom Rooms; Cloud service providers including Microsoft Teams Admin Center and Zoom Device Management |
| | Integrated People Count | Yes |
| **Ease of use** | Appliance mode | Yes |
| | BYOD mode | Yes |
| | Digital pan/tilt/zoom | Yes |
| | Manual Pan-Tilt-Zoom (PTZ) | Yes |
| | One touch meeting join | Yes |
| | Camera privacy cover | Yes |
| **Extended info** | Operating temperature | 5°C to 35°C \| 41°F to 95°F |
| | Operating humidity | 15% to 80% |
| | Storage temperature | -20°C to 60°C \| -4°F to 140°F |
| | Maximum altitude | 4876.8m \| 16000ft |
| | Proximity sensor | Yes |

| Jabra Control IP | Main unit dimensions (WxHxD) | 248.2 x 169.2 x 50.3 mm \| 9.77 x 6.66 x 1.98 in |
| --- | --- | --- |
| | Main unit weight | 670.72g \| 23.63oz |
| | Display size | 10.1" |
| | Display orientation | Landscape |
| | Display resolutions | 1920 x 1200 |
| | PoE | Yes |
| | Power over ethernet (PoE) | IEEE 802.3af |
| | Position angle | 0° / 25° |
| | Kensington lock compatible | Yes |

| Products | 8720-232 | Jabra PanaCast 40 VBS - UC |
| --- | --- | --- |
| | 8721-232 | Jabra PanaCast 40 VBS - MS Teams Room |
| | 8722-232 | Jabra PanaCast 40 VBS - Zoom Room |

Note: Table stand sold separately.

[1] Partner specific.

[2] Used for Microsoft Proximity Join and to trigger Teamcast (Microsoft) or Airplay (Zoom)

Please note: The information presented in this document is provisional as of December 2024 and is subject to change without notice. Jabra does not accept any liability for any inaccuracies or omissions in this document and any decisions you make based on this information are your sole responsibility.

**Jabra PanaCast 40 VBS Tech Sheet 06032025**

Download the latest version of this document at:
jabra.com/support